

WHEEL LOADER FL18

WHEEL LOADER WITH Standard Bucket, Kubota Engine, 31*15.5-15 Tires, Closed Cabin, Italy Hydrostatic Driving system, Inching Function, BOBCAT QUICK HITCH, Special Axles with Differential Lock for Hydrostatic Transmission System, Seat, Adjustable Steering Wheel, Electrical Joystick, Floating Function, Pressure Checking System, Free Parts for service. E4 Lamp, LED Working Light, LED Alarm Light YELLOW RAL1003, GREY RAL7015 SPARE PARTS.





Options:

E4 Lamp	Bobcat Quick Hitch
LED Working Light	Euro Quick Hitch
LED Alarm Light	Trima Quick Hitch
One more Extra Hydraulic Line	3 Point Hitch
Trailer Ball	Varta Anti-Freeze Battery
Extra Electric Line	Loader Damper
Tyre Chains	Closed Cabin
Kubota D1703 EURO5 Engine	

Attachments:

Pallet Forks	V-snow Blade
Adjustable Pallet Forks	Crops Blade
Grapple Forks	Bale Grab
European Grapple Forks	Drum folder
Wooden Forks	Sweeper
Manure Forks	Sweeper with Collector
Grapple Bucket	400mm Auger
4 in 1 bucket	Hammer
Light Bucket	Digger
Snow Bucket	Digger with Thumb
Snow Bucket with Wings	JIB
Mixer Bucket	Hay Forks with single fork
Rock Bucket	Hay Forks with double fork
Crops Bucket (1.6cbm)	Double-blade Bucket
Salt Spreader	High-dumping Bucket
Snow Blade	360 Degree Wooden Forks

Specifications:

Performance	Rated loading (lbs.)	2204
	Overall weight (lbs.)	5511
	Rated bucket capacity (yd ³)	0.49
	Maximum tractive force (kN)	17
	Maximum breakout force (kN)	19
	Maximum grade ability (°)	20
	Maximum dump height(mm)	2029
	Maximum dump reach(mm)	608
	Overall dimension (L×W×H) (mm)	4210*1310*2316
	Minimum turning radius (outside of wheels) (mm)	3336
Engine	Oscillation angle	8°
	Model	KUBOTA V1505
	Type	Inline water cooled, four strokes
	Displacement(L)	1.498
	Rated power(Hp)	24.8
	Rated speed (r/min)	2300
Transmission system	Maximum torque N.m @speed	92.6@1700
	Type	Closed piston pump
	Gear shift	Electric, Stepless
	Maximum speed	18km/h
Drive axles	Main reducing mode	Bevel gear grade 1 reduction
	Wheelbase (mm)	1550
	Wheel tread(mm)	930
	Ground clearance(mm)	240
Hydraulic system	System working pressure (Mpa)	18
	Boom lifting time (s)	3.2
	Total time (s)	6.3
	Fuel tank capacity (L)	40
	Function of leveling automatically	yes
Brake system	Service brake	Drum brake
	Parking brake	Manual drum brake
Tyre	Type specification	31*15.5-15
	Front tyre pressure (kPa)	350
	Rear tyre pressure (kPa)	350