



Canada Mining Machinery Sales Ltd

Canada Mining Machinery Sales Ltd

#70 Haist Ave., Vaughan, L4L 5V4, ON

+437 669 9966 / 437661166

cmmsdirector@gmail.com

www.cmmss.ca www.lovol-canada.ca

FSL15 TELESCOPIC WHEEL LOADER

TELEHANDLER, Italy Hydrostatic Transmission, Standard Bucket, Perkins 403J-17 Engine(Euro5 & EPA4), France Brand 4 Wheel Driving Motors, Eaton steering Motor, Rops&Fops Cabin, Comfortable And Safe Seat, Electric Joystick, Bobcat Quick Hitch, Led Working Lights, Electric Hand Brake, 26*12-16.5 Tyre. E4 Lamp, Seat with Shock Absorption and Weight Adjustment.





Options:

E4 Lamp	Change Color
Overload Alarm System	Seat with Shock Absorption and Weight Adjustment
Tyre Chain (only front tyre)	Bobcat Quick Hitch

Attachments :

Pallet Forks	European Grapple Forks
4 in 1 Bucket	Grapple Forks
Grapple Bucket	Hydraulic Adjustable Pallet Forks
Light Bucket	Bale Grab/ Barrel Clamp

Specifications:

Engine Details	
Model:	Perkins EURO 5 engine
Engine Type:	In-line arrangement, water-cooled, three-cylinder diesel engine
Rated Power:	24.67 HP
Rated Speed:	2200 r/min(rpm)
Fuel Consumption ration in standard working condition:	230g/kw.H
Transmission System	Hydraulic Motor + 4 Wheel Drive Motors
Standard Bucket:	
Bucket capacity:	0.39 yd3
Bucket Width:	1588mm
Bucket type:	Standard
Rated load:	3086 lbs, including attachment
Overall Dimensions:	
Overall length(bucket on ground)	3350mm
Overall Height	1955mm
Overall width	1588mm
Max. lifting Height	4010mm

Operating Specifications:	
Steering system:	Rear axle with hydraulic power steering
Min. turning radius:	3560mm
Driving system:	Hydraulic Motor, Four Wheel Drive.
Operating Weight:	6172.943 lbs.
Max. Driving Speed:	18km/h
Other	Quick Coupling System; Joystick; Self-levelling
Brake System	
Service Brake	Hydraulic Oil Cutting-Off Brake
Parking Brake	Electrical Parking Brake
Tyre	
Model	26*12-16.5
Width	275mm
Diameter	658mm
Wheelbase	1720mm
Track	1150mm
System Pressure	
Driving system	35Mpa ; 46cc
Work system	24Mpa ; 22L/min